

## TECHNICAL DATA

# PLS 180G RBP Green Cross Line Laser Level Kit



## Key features

- Accuracy:  $\pm 1/8$  in at 30 ft. ( $\pm 3$  mm @ 10 m)
- Green beam laser
- Horizontal fan angle: 180 °
- Vertical fan angle: 130°
- Durable pendulum lock
- IP54 rating to limit dust and water entry for years of operation on the job site.

## Product overview: PLS 180G RBP Green Cross Line Laser Level Kit

The PLS 180G RBP green laser level offers the durability and precision you expect from Pacific Laser Systems. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly. Use the pendulum lock to secure the laser during transport or if dropped.

- This self-leveling cross line laser level is equipped for multiple applications including wall construction, acoustic ceiling installation, tile installation, residential and commercial construction.
- Includes magnetic L-bracket for fast, easy overhang and center- line measurements and the UB9 Universal Wall/Ceiling Bracket for fine vertical adjustment and ceiling installation.
- Maximize your laser level operating time up to 3x and eliminate alkaline battery purchases

## Specifications: PLS 180G RBP Green Cross Line Laser Level Kit

<b>Rotary levels</b>	PLS 180G
<b>Baery</b>	RBP5 Rechargeable Baery Pack
<b>Baery Life, Continuous Use</b>	30 hours (with RBP5 Baery Pack)
<b>Line Fan Angle</b>	
Horizontal	= 180°
Vertical	= 130°
<b>Working Range</b>	
Point Laser (6 only)	=30 m (100 ft.)
<b>Line Laser</b>	
Without SLD	=15 m (50 ft.)
With SLD	6 m to 60 m (20 ft. to 200 ft.)
<b>Accuracy</b>	=3 mm @ 10 m (=1/8 in at 30 ft.)
<b>Laser Leveling</b>	
System	Automatic, Pendulum
Range	4°
<b>Line Laser Width</b>	=2 mm at 5 m
<b>Temperature</b>	
Operating	-10 °C to 50 °C (14 °F to 122 °F)
<b>Storage</b>	
With Baeries	-18 °C to 50 °C (-0.4 °F to 122 °F)
Without Baeries	-20 °C to 70 °C (-13 °F to 158 °F)
<b>Relative Humidity</b>	0 % to 90 % (0 °C to 35 °C)
	0 % to 75 % (35 °C to 40 °C)
	0 % to 45 % (40 °C to 50 °C)
<b>Size (H x W x L)</b>	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)
<b>Weight</b>	~ 0.6 kg (1.3 lb.)
<b>Safety</b>	IEC 61010-1: Pollution Degree 2
<b>Laser</b>	IEC 60825-1:2014 Class 2
<b>Light Source</b>	Semiconductor laser diode
<b>Max Output Power</b>	< 1 mW
<b>Wavelength</b>	525 nm ± 5 nm
<b>Electromagnetic compatibility (EMC)</b>	

Inteational	IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B
	Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the inteal function of the equipment itself.
	Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes.
	Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object
Korea (KCC)	Class B Equipment (Broadcast communications equipment for home)
USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.

## Ordering information



### **PLS 180G RBP KIT**

PLS 180G RBP KIT, Cross Line Green Laser Kit

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2025 Fluke Corporation.  
Specifications subject to change without notice.  
05/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**